MAINTENANCE SERVICE - EVERY 10,000 MILES



All 1974 Models (With #3Z At 30,000 Mile Intervals)

Customer:	Work Order No.:					
Address:	License No.:					
City & State:	Mileage:					
Zip Code or Province:	Time Promised:					
Maintenance Work to be Performed: MB Maintenance Service (three sections) with engine oil change and oil filter service. Oil: Brand-Viscosity	Special Maintenance Work Performed at Extra Cost: Sliding Roof: Clean guide channels and lubricate lightly. Lighting System: Check headlights and aim. Battery: Clean housing and terminals; grease terminals lightly. Paint finish and chrome care. Clean Engine and Engine Compartment: lubricate all control linkages. Special Instructions from Customer:					
Visual Inspection: Check For Leakage and General Condi	tion.					
☐ Engine ☐ Rear Axle	☐ Front Axle ☐ Undercarriage					
☐ Steering ☐ Brakes	☐ Tires ☐ Body Condition					
☐ Transmission ☐ Shock Absorbers	☐ Exhaust System					
Result:						
Part I: Service Maintenance with Oil Filter Change						
-280 ALL	240 D 230 280-280C 450-ALL					
240D 280-280C 280-280C Oil Change	240 D 230 280-28					
☐ ☐ ☐ 151 Engine oil with filter change.	O41 Fuel hoses and pipes.					

MBNA/MBC 2023 (Rev. 5-83) Printed in USA

□ □ □ □ 038 Heating & cooling system.

Drain engine oil cooler.

Inspection for Leaks and Condition

(continued)

045 Clutch operating mechanism

766 Throttle valve, clean (California only)

(manual transmission only).

987 Correct tire air pressure.

Date __

	 706 Parking brake: re-adjust. 028 Front axle ball joints: Check for developed play and rubber boot for leak tightness. 029 Steering: check for sealing and condition of sealing collars and steering rods. 	O 98 Road test or dynamometer Clutch. Manual transmission. Automatic transmission. Air conditioner. O 97 Brake test on test stand/road.					
	Retightening of Nuts, Bolts, and Retaining Parts 924 Steering gear mounting screws (3). 988 Wheel bolts. 099 Check function of: Headlights, rear lights and stop lights. Directional signals: Hazard warning lights. Windshield wipers, windshield washer. Heating and ventilation.	Tire tread depth and brake performance Front—Left Front—Right IN. KP IN. KP Rear—Left Rear—Right IN. KP IN. KP			- Right KP Right		
240 D 230 280-280C M 450-All	ntenance Oil Change	240D 230 280-280C 280-280C 280-80C	#3Z	of Nuts and	Bolts		
	Filter Replacement or Cleaning 174 Automatic transmission: replace filter element. 612 Power steering: Replace filter element. 851 Fuel feed pump: clean screen (carburetor engines only). 840-847-849 Fuel filter: clean element or replace 845 Fuel main filter: Clean filter element and filter housing 844 Fuel pre-filter: check 813 Check throttle control linkage.		flange to Exhaus: 876 Carbur Checking 501 Check of transmi 625 Check f 030 Check p	 871 Intake and exhaust manifold nuts and exhaust flange bolts. Exhaust pipe flange only. 876 Carburetor mounting flange screws Checking 501 Check clutch lining thickness (manual transmission only). 625 Check front wheel toe-in. 030 Check propeller shaft joint discs for wear or damage. 			
	Lubrication 388 Front wheel grease caps: clean and refill with new grease.						

Service Manager (Signature) __